


TRACK LIGHT

SERIES KTL 365 A/B/C ADJUST




KTL-365A 12W




Parameter	Value
Model	KTL365A12WW/B
Rate Power	12W
Luminous Flux	1,080lm
Luminous Efficiency	90lm/W
Color Temperature	CCT 3000K/ 4000K/6000K
Input Voltage	AC 185-260V , 50/60Hz
Beam Angle	10° - 50°
Dimensions	73*104 mm

KTL-365B 20W



Parameter	Value
Model	KTL365A20WW/B
Rate Power	20W
Luminous Flux	1,800lm
Luminous Efficiency	90lm/W
Color Temperature	CCT 3000K/ 4000K/6000K
Input Voltage	AC 185-260V , 50/60Hz
Beam Angle	10° - 50°
Dimensions	88*110 mm

KTL-365C 30W



Parameter	Value
Model	KTL365C30WW/B
Rate Power	30W
Luminous Flux	2,700lm
Luminous Efficiency	90lm/W
Color Temperature	CCT 3000K/ 4000K/6000K
Input Voltage	AC 185-260V , 50/60Hz
Beam Angle	10° - 50°
Dimensions	100*116 mm

KTL-01 = DIMMABLE
KTL-02 = NON-DIM



WHITE



BLACK

