

POWER SUPPLY

SERIES LPV



APPLICATION / DESCRIPTION

- ◆ Industrial automation machinery
- ◆ Industrial control system
- ◆ Mechanical and electrical equipment

20W – 150W



Parameter		MODEL				
		LPV-20-24	LPV-35-24	LPV-60-24	LPV-100-24	LPV-150-24
Output	Rated Power	20W	35W	60W	100W	150W
	Rated Current	0.84A	1.5A	2.5A	4.2A	6.3A
	DC voltage	24V				
AC input voltage range		90~264VAC		90~264VAC : 120-370CDV		180~305VAC
AC inrush current (max)		Cold start, 70A at 230 VAC	Cold start, 55A at 230 VAC	Cold start, 60A at 230 VAC	Cold start, 70A at 230 VAC	Cold start, 60A at 230 VAC
Overload Protection	Range	110% ~ 150%				
	Type	Hiccup mode , auto-recovery				
Overload Protection	Range	115%~ 135% Rated output voltage				
Working temperature		-30 ~ +70℃	-30 ~ +65℃	-30 ~ +70℃	-25 ~ +70℃	-25 ~ +65℃
Dimension (LxWxH) mm		118x35x26	148x40x30	162.5x42.5x32	190x52x37	191x63x37.5