




FLOOD LIGHT SERIES KFD-S


- ◆ High performance design with multi-chips Package 5050 LED source and Exclusive Lens to satable per-formance, low light failure and no dead light
- ◆ High pressure die cast aiuminium alloy housing.
- ◆ Anti-corrosion with electrophoresis process.




10W,20W



30W,50W



80W,100W



150W,200W

Parameter	Value							
Model	KFDS10W	KFDS20W	KFDS30W	KFDS50W	KFDS80W	KFDS100W	KFDS150W	KFDS200W
Rate Power	10W	20W	30W	50W	80W	100W	150W	200W
Luminous Flux	1,300lm	2,600lm	3,900lm	6,500lm	10,400lm	13,000lm	19,500lm	26,000lm
Luminous Efficiency	130lm/w							
Color Temperature	CCT 3000K/4000K/5000K/5700K							
Color Rendering Index	> 80 Ra							
Input Voltage	AC 100-277 VAC , 50/60Hz							
Power factor	> 095							
Beam Angle	120°							
Work Temperature	-20°C to +50°C							
Work Life	> 50,000 Hours							
Heat sink	Aluminum							
IP Rating	IP65							
Net Weight	0.69 kg	2.02 kg		4.26 kg		6.68 kg		
Dimensions	173*168*40.5 mm		263.5*280.4*44 mm		354*367.6*57.5 mm		440.5*493.6*63 mm	