

ACCESSORIES

ACCESSORIES

Classic RF Remote Controller



R6-1+V1 Blister

MODEL : R6+V1 Blister

Input voltage : 5-36VDC

Max load current : 1CH*8A, Max 12A, 1 zone

Max load power : 40W/96W/192W/288W
(5V/12V/24V/36V)

Dimensions (mm) : L150xW125xH23



R7-1+V2 Blister

MODEL : R7+V2 Blister

Input voltage : 12-24VDC

Max load current : 2CH*5A, Max 10A, 1 zone

Max load power : 120W/240W
(12V/24V)

Dimensions (mm) : L150xW125xH23



R8-1+V3 Blister

MODEL : R8+V3 Blister

Input voltage : 12-24VDC

Max load current : 3CH*4A, Max 12A, 1 zone

Max load power : 144W/288W
(12V/24V)

Dimensions (mm) : L150xW125xH23



R8-1+VP Blister

MODEL : R8-1+VP Blister

Input voltage : 12-24VDC

Max load current : 4CH*3A, Max 12A, 1 zone

Max load power : 144W/288W
(12V/24V)

Dimensions (mm) : L150xW125xH23



R17+V5M Blister

MODEL : R17+V5M Blister


Input voltage : 12-24VDC

Max load current : 5CH*3A, Max 15A, 1 zone

Max load power : 180W/360W
(12V/24V)

Dimensions (mm) : L150xW125xH23

LED CONTROLLER



V1

MODEL : V1

Input voltage : 5-36VDC

Output current : 1CH*8A, Max 12A

Output power : 40W/96W/192W/288W
(5V/12V/24V/36V)

Dimensions (mm) : L97xW33xH18



V2

MODEL : V2

Input voltage : 12-24V DC

Output current : 2CH*5A, Max 10A

Output power : 120W/240W
(12V/24V)

Dimensions (mm) : L97xW33xH18



VP

MODEL : VP

Input voltage : 12-24V DC

Output current : 3CH*4A, Max 12A

Output power : 144W/288W
(12V/24V)

Dimensions (mm) : L114xW38xH20